

Application for
UNITED STATES LETTERS PATENT

Of

SEIICHI HIGAKI

and

HISAO HONMA

For

MEMORY CONTROL DEVICE AND METHOD FOR CONTROLLING THE SAME

- 1 -

MEMORY CONTROL DEVICE AND METHOD FOR
CONTROLLING THE SAME

CROSS-REFERENCE TO RELATED APPLICATION

This application relates to and claims
priority from Japanese Patent Application No. 2003-
428624, filed on December 25, 2003, the entire
5 disclosure of which is incorporated herein by
reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a technique
10 for controlling writing and reading of data from a
upper device in a storage control device equipped with
a plurality of disk drives.

Description of the Related Art

There are hitherto the transaction and
15 database as principal applications of the storage
control device such as a disk array system. In such
applications severe requirements are thus imposed as
regards high performance and high reliability.
Therefore, the storage control device used for this
20 application is equipped with a hard disk drive (HDD)
with high performance and high reliability. As the HDD
fully complying with the imposed requirements must be

highly reliable as one of parts, it would be usually highly expensive.

A technique for saving dissipation power of the disk array system equipped with such HDD's has been
5 proposed.

Such a technique is disclosed in, for example, JP-A-2000-293314.

However, such a technique of the prior art is not effective for the disk array system or storage
10 control device used for the applications such as back-up, restore, archive and the like.

SUMMARY OF THE INVENTION

In order to solve the problems described above, the present invention has the following
15 features.

A upper device in the present invention comprises application programs, control programs, user interfaces, application interfaces and host bass adapters. Respective configurations and processing
20 flow charts will be explained in paragraphs describing the mode for carrying out the invention.

The storage control device according to the present invention comprises channel adapters, memories, disk adapters, a connecting device and a plurality of
25 disk drives.

The channel adapter is connected to the upper device so that the channel adapter provides a first

logical volume to the upper device and receives data which are sent from the upper device to the first logical volume.

The memory is connected to the channel
5 adapter and stores data exchanged between the memory and the upper device, control information concerning the data exchanged between the memory and the upper device, and the configuration information concerning the configuration of the storage control device.

10 The disk adapter controls in a manner that data sent from the upper device to a first logical volume are read from the memory and written on the memory as data addressed to second logical volume corresponding to the first logical volume. The second
15 logical volume is used as a region for storing the data in transmission and reception of the data between the channel adapters and the disk adapters.

The connecting device is connecting between the channel adapters, memory and disk adapters.

20 A plurality of disk drives are connected to the disk adapters so that the data to the second logical volume are written on the disk drives as data group having a redundant relation by controlling of the disk adapters.

25 The channel adapter has processors to provide to the upper device a logical volume for control which is utilized when the configuration information in the memory is read by the upper device. The processor of

the channel adapter causes other second logical volume instead of the second logical volume to correspond to the first logical volume in response to a change-over indication issued from the upper device to the logical
5 volume for control and causes to operate spindle motors of a plurality of disk drives on which data group corresponding to the second logical volume and having the redundant relation is written.

The processor of the channel adapter causes
10 to stop the spindle motors of a plurality of disk drives on which data group corresponding to the second logical volume to be changed in response to the change-over indication and having the redundant relation is written.

15 The processor of the channel adapter judges whether spindle motors of the plurality of disk drives are operating or not, on which disk drives data group corresponding to the another second logical volume designated by the change-over indication and having the
20 redundant relation is written, and if the spindle motor is operating, to cause the operation to continue, and if the spindle motor is not operating, to cause to operate the spindle motor of the plurality of disk drives on which data group corresponding to the another
25 second logical volume and having the redundant relation is written.

If one corresponding to the another second logical volume corresponding to the other first logical

volume provided to the upper device exists in the plurality of disk drives on which data group corresponding to the second logical volume to be changed in response to the change-over indication and
5 having the redundant relation is written, the processor of the channel adapter causes the operation of the plurality of disk drives to continue on which drives data group corresponding to the second logical volume to be changed in response to the change-over indication
10 and having the redundant relation is written.

If one corresponding to the other second logical volume corresponding to the other first logical volume provided to the upper device does not exist in the plurality of drives on which the data group
15 corresponding to the second logical volume to be changed in response to the change-over indication and having the redundant relation, the processor of the channel adapter causes to stop the operation of a plurality of disk drives on which disk drives the data
20 group corresponding to the second logical volume to be changed in response to the change-over indication and having the redundant relation is written.

If the kind of command sent from the upper device to the logical volume for control is a write
25 command, the processor of the channel adapter writes the content of the write command on the logical volume for control and judges the content of the write command to be the change-over indication.

In the case that the kind of the command sent from the upper device to the logical volume for control is a read command, the processor of the channel adapter judges the read command to be a configuration
5 information, and reads the configuration information from the memory and send it to the upper device.

In the case that a command sent from the upper device is the command addressed to the first logical volume, the processor of the channel adapter
10 judges the command sent from the upper device to be a command concerning writing or reading of data, and also in the case that the command sent from the upper device is the command addressed to the logical volume for control, the processor judges the command sent from the
15 upper device to be a command concerning the control information.

Although the processor of the channel adapter performs various kinds of control in the above description, other control processor, for example, the
20 processor of the disk adapter may preferably carry out the control the same as that described above. Moreover, it is preferable that the processor of the channel adapter and the processor of the disk adapter carry out the control the same as the control described
25 above in cooperation with each other.

More detailed configuration and processing flow chart will be explained in paragraphs of mode for carrying out the invention later.

According to the present invention, the effective controlling method can be provided for disc array systems or storage control devices used for the applications as back-up, restore and archive.

5 We intend to effect the back-up, restore and archive of data at a high speed in a short period of time in consideration of various elements such as increased capacity of data memorized in the storage control device, variety of kinds thereof and operations
10 around the clock. Therefore, we contemplate the back-up, restore and archive using the storage control device equipped with HDD's as storage mediums for the field in which the back-up and restore of data and archive are carried out by tape drives, as well. In
15 such applications, as large capacity is particularly required, the requirement imposed upon the storage control device is to provide great capacity of memory at much less expensive.

 In order to reply to the requirement, we
20 intended to utilize the HDD using the serial ATA (S-ATA) as interconnection interface which has been used in less expensive desktop PC, at the sacrifice of the performance and reliability to some extent.

 As the HDD using fiber channel as
25 interconnection interface is predetermined to be provided in the host computer operating as a server, the HDD is inherently designed to operate around the clock. In contrast herewith, as the HDD using S-ATA as

interconnection interface is predetermined to be provided in the disk top PC and the like, the HDD is inherently designed to be used only a few hours every day.

5 In the HDD using S-ATA as interconnection interface, therefore, the mean time between failures (MTBF) which is one index of reliability is in general designed to be shorter in comparison with the HDD using fiber channel as interconnection interface. According-
10 ly, the HDD using S-ATA as interconnection interface is prone to failures in comparison with the HDD using fiber channel as interconnection interface, when the spindle motor of the HDD is always rotated as in the operation around the clock.

15 On the other hand, it is unlikely that the access to the HDD as a storage medium always occurs in the application of the HDD to the back-up, restore and archive. In back-up or restore, for example, writing of data onto the storage control device would occur
20 once or a few times a day, only when the back-up is obtained, and reading of data from the storage control device would occur very rarely, only when restoring. In the use of the archive, moreover, writing of data onto the storage control device would occur only when
25 the archive is obtained, while reading of data from the storage control device would occur only when archived data are rarely referred.

 In the storage control device used for

applications of the back-up, restore and archive in this manner, the access to data of storage medium does not occur frequently so that it is effective for the spindle motor of the HDD having the data stored therein
5 to stop in the case that no access to the data occurs evidently.

Other objects, features and advantages of the invention will become apparent from the following description of the embodiments of the invention taken
10 in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an example of the hardware configuration of the storage control device envisioned in the embodiment of the present invention;

15 FIG. 2 is one example of the correspondence of the hardware configuration and logical configuration of the storage control device envisioned in the embodiment of the present invention;

FIG. 3 is one example of the method for
20 reading the configuration information by the logical configuration of the storage control device envisioned in the embodiment of the present invention;

FIG. 4 is one example of configuration information table held in the storage control device of
25 the embodiment according to the invention and used for managing correspondence between the numbers of the host logical volumes and the internal logical volumes;

FIG. 5 is one example of configuration information table held in the storage control device of the embodiment according to the invention and used for managing correspondence between the numbers of the ECC groups and the numbers of the internal logical volumes provided by the ECC groups;

FIG. 6 is one example of flow chart of the program operating in the channel adapters of the embodiment according to the present invention;

10 FIG. 7 is one example of the method for changing the correspondence between the host logical volume and the internal logical volume in the storage control device envisioned in the embodiment of the present invention;

15 FIG. 8 is one example of flow chart for changing the correspondence between the host logical volume and the internal logical volume by the program operating in the channel adapter of the embodiment according to the present invention;

20 FIG. 9 is one example of configuration information table held in the storage control device in the embodiment of the present invention and used for managing the correspondence between the numbers of the ECC groups including HDD having the rotating spindle motor and the numbers of the internal logical volumes included in the ECC groups;

FIG. 10 is one example of configuration information table held in the storage control device of

the embodiment according to the present invention and used for managing the correspondence between the numbers of the ECC groups including HDD having the rotating spindle motor and the numbers of the internal
5 logical volumes included in the ECC groups; and

FIG. 11 is one example of the method for reading the configuration information by the logical configuration of the storage control device envisioned of the embodiment according to the present invention.

10 DETAILED DESCRIPTION OF THE EMBODIMENTS

The control method for a disk array system without continuous operation of a spindle motor of HDD in consideration of the service life of the HDD using the S-ATA as an interconnection interface will be
15 explained with reference to the drawings hereinafter.

According to the aspect for carrying out the invention, it will be expected that the time until occurrence of fault, which is presumed by the MTBF, can be prolonged by performing the control for stopping the
20 spindle motor of the HDD, in comparison with the case using the spindle motor of the HDD without its stoppage.

FIG. 1 illustrates a configuration of the storage control device. Reference numeral 1-1 shows
25 the storage control device and numeral 1-2 denotes a host computer connected to the storage control device. The storage control device 1-1 is equipped with a

plurality of channel adapters 1-3. Each of the channel adapters 1-3 has a port 1-4 through which the channel adapter 1-3 is connected to a host bus adapter (HBA) 1-5 equipped in the host computer by means of, for
5 example, a fiber channel.

The storage control device 1-1 is equipped with a plurality of hard disk drives (HDD) 1-6 as storage mediums. The storage control device 1-1 is further equipped with a plurality of disk adapters 1-7
10 for controlling the plurality of HDD's 1-6. The disk adapters 1-7 each have a port 1-8 for connecting the HDD's, by means of which the disk adapters 1-7 are connected to the plurality of HDD's 1-6. The ports 1-8 and the plurality of HDD's 1-6 are each connected by
15 FC-A1 of fiber channel, fabric or parallel SCSI or ATA or S-ATA.

The channel adapters 1-3 are each connected to the disk adapter 1-7 to each other through an interconnection portion 1-9 to which a shared memory 1-
20 10 as well as a cache memory 1-11 are connected. The channel adapters 1-3 and the disk adapters 1-7 are each equipped with a microprocessor 1-12, 1-14 and a local memory 1-13, 1-15 in a pair. In the microprocessor 1-12 on the channel adapter 1-3, the program is executed
25 for processing the command sent from the host computer 1-2. In the microprocessor 1-14 on the disk adapter 1-7, the program is executed for controlling the plurality of HDD's 1-6. The program is operated by the

use of the local memory, respectively. In order to carry out processing in cooperation of the plurality of channel adapters 1-3 with the plurality of disk adapters 1-7, control information which must be shared with one another is put in the shared memory 1-10. It is possible for the microprocessor 1-12 on each of the channel adapter 1-3 and the microprocessor 1-14 on each of the disk adapter 1-7 to access the control information in the shared memory through the interconnection portion 1-9.

The cache memory 1-11 serves to temporarily store data which the host computer 1-2 may access. As the cache memory 1-11 can access data at a faster rate than HDD 1-6, the cache memory 1-11 contributes to improvement in the access performance (particularly responsibility to commands) of the storage control device.

The left hand of FIG. 2 is a view explaining the storage control device 1-1 described in FIG. 1 from the viewpoint of its physical configuration (a simplified view of FIG. 1). In contrast herewith, the right hand of FIG. 2 is a view explaining the storage control device 1-1 from the viewpoint of its logical configuration. FIG. 2 is a view for explaining a mapping between the physical configuration and the logical configuration.

A few of HDD's among the plurality of HDD's 2-6 are assembled to form an Error Check and Correction

group (ECC group) 2-12. The ECC group is constituted as redundant array of independent disks (RAID) and protects data memorized from single-point fault of HDD in the ECC group.

5 The storage region formed by the ECC group is divided into one or plural regions to produce internal logic volumes. In the example shown in FIG. 2, one ECC group 2-12 is divided into two regions to produce two internal logical volumes 2-13 and 2-14. The internal
10 logical volumes 2-13 and 2-14 are logical volumes provided by the program executed in the microprocessor (1-14 in FIG. 1, not shown in FIG. 2) in the disk adapter 2-7.

 In order that the host computer 2-2 reads and
15 writes data out and on the storage control device 2-1, it is required that the host computer 2-2 has recognized the host logical volumes 2-15 and 2-16 provided by the storage control device 2-1.

 The host logical volumes 2-15 and 2-16 are
20 logical programs which are provided to the host computer 2-1 by programs executed in the microprocessors (1-12 in FIG. 1, not shown in FIG. 2) in the channel adapters 2-3. For example, fiber channels and Logical Units (LU) in SCSI may map to the host logical volumes.

25 The host logical volumes 2-15 and 2-16 themselves are imaginary ones not having actual memory regions. The host logical volumes and the internal logical volumes map to one to one, respectively. The

host logical volume 2-15 maps to the internal logical volume 2-13 having an actual memory region for memorizing data, while host logical volume 2-16 maps to the internal logical volume 2-14, respectively.

5 The mapping of the host logical volume and internal logical volume is stored as a configuration information in the shared memory 2-10 and controlled by the program executed in the microprocessor (1-12 in FIG. 1, not shown in FIG. 2) in the channel adapter 2-10 3.

 The data written from the host computer onto the host logical volume are written onto the internal logical volume having the actual memory region according to the mapping between the host logical volume and the internal logical volume. Namely, for 15 example, the data that the host computer 2-2 wrote on the top logical block of the host logical volume 2-15 through the port 2-17 are actually written on the top logical block of the internal logical volume 2-13.

20 Similarly, for example, the data that the host computer 2-2 wrote on the 100th logical block from the top of the host logical volume 2-16 are actually written on the 100th logical block from the top of the internal logical volume 2-14.

25 FIG. 3 is a view newly drawn by further adding the details to the logical configuration of the storage control device explained in connection with the right hand of FIG. 2 for disclosing the present

invention.

The storage control device 3-1 includes three ECC groups 3-3 to 3-5. In the memory region formed by the three ECC groups 3-3 to 3-5, four internal logical
5 volumes 3-6 to 3-9 are formed. The internal logical volume 3-6 exists in the ECC group 3-3, the internal logical volume 3-7 in the ECC group 3-4, and the internal logical volumes 3-8 and 3-9 in the ECC group 3-5, respectively.

10 The storage control device 3-1 has two kinds of host logical volumes. The host logical volume (for data) of the one kind is used to store the data that are recognized by the host computer 3-2 and to be used by the application program 3-12 in the host computer 3-
15 2. The host logical value (for control) of the other kind will be explained later. A plurality of the host logical volumes (for data) and a plurality of the host logical volumes (for control) can exist in the storage control device 3-1, respectively. FIG. 3 illustrates
20 the host logical volume (for data) 3-10 and host logical volume (for control) 3-11 as representative of these volumes.

In FIG. 3, there are four internal logical volumes 3-6 to 3-9 for one host logical volume (for
25 data) 3-10. A mapping change portion 3-13 is provided between the host logical volume (for data) 3-10 and the four internal logical volumes 3-6 to 3-9. The mapping change portion 3-13 serves to change the mapping

between the host logical volume (for data) 3-10 and the internal logical volumes 3-6 to 3-9 according to the indication from a mapping change and power control portion 3-14.

5 The mapping between the host logical volume and the internal logical volume is controlled by a program executed by the microprocessors in the channel adapters. Therefore, both the mapping change portion 3-13 and the mapping change and power control portion
10 3-14 are realized by this program.

For example, when the host logical volume (for data) 3-10 is in the mapping relation to the internal logical volume 3-6, the data written on the top logical block of the host logical volume (for data)
15 from the host computer 3-2 through the port 3-15 are in fact written on the top logical block of the internal logical volume 3-6.

Similarly, for example, when the host logical volume (for data) 3-10 is in the mapping relation to
20 the internal logical volume 3-9, the data written on the top logical block of the host logical volume (for data) from the host computer 3-2 through the port 3-15 are written on the top logical block of the internal logical volume 3-9.

25 A configuration information 3-17 holding the logical configuration of the storage control device is memorized in part of the shared memory 3-16 in the storage control device 3-1. The configuration

information includes a table for holding the mapping of the numbers of the host logical volumes and the numbers of the internal logical volumes in mapping relation to the host logical volumes as exemplarily shown in FIG. 4
5 and a table for holding the numbers of ECC groups and the numbers of the internal logical volumes included in the ECC groups as exemplarily shown in FIG. 5.

The change mapping between the host logical volume and the internal logical volume in the storage
10 control device will be then explained in connection with the indication from the host computer 3-2. There are two methods for changing the mapping between the host logical volume and the internal logical volume.

One method is carried out by the indication
15 issued from the application program 3-1 in the host computer 3-2.

This method includes roughly two steps.

In the step 1, the application program takes, from the configuration information 3-17 in the storage
20 control device 3-1, the information of 1) configuration of the host logical volumes, 2) configuration of the internal logical volumes and 3) mapping between the host logical volume and the internal logical volume.

This step 1 is carried out by the application
25 program if required. For example, the step 1 is performed when the application program 3-12 is started or by an evident indication effected when an operator of the application program 3-12 knows a variation of

the physical or logical configuration of the storage control device 3-1.

In the step 2, the application program 3-12 performs the change mapping between the host logical
5 volume and the internal logical volume on the basis of the configuration information of the storage control device 3-1 taken in the application program 3-12 in the step 1. The step 2 is also carried out by the application program 3-12 if required.

10 First, the operation of the step 1 will be explained.

An application program interface (API) 3-18 is called in order that the application program 3-12 to be executed in the host computer 3-2 takes the
15 configuration information 3-17 which the storage control device 3-1 has. The API 3-18 is provided by a control program 3-19 which is also executed in the host computer 3-2. The control program 3-19 is a program having a function issuing an indication to the
20 configuration information reading portion 3-20 for reading out configuration information 3-17 and a function issuing an indication to the mapping change and power control portion 3-14 for changing the mapping between the host logical volume and the internal
25 logical volume.

The control program 3-19 can access another kind of host logical volume (for control) 3-11 (to be explained later) in the storage control device 3-1

through the HBA 3-21 and the port 3-15. This host logical volume (for control) 3-11 does not store the data of the application program but is used to control the storage control device 3-1. The term "control" is
5 here understood as signifying the function for reading out the configuration information 3-17 and the function for changing the mapping between the host logical volume and the internal logical volume.

The interior of the host logical volume (for
10 control) 3-11 is divided in plurality of regions. A particular function is determined with respect to each region. For example, the region 3-22 is used for reading out the configuration information 3-17. When the logical block assigned in the region 3-22 is read
15 out by the host computer 3-2, in concrete terms, by the control program 3-19, the configuration information 3-17 is included in the block.

For example, moreover, the region 3-23 is used for the function for changing the mapping between
20 the host logical volume and the internal logical volume, so that the mapping between the host logical volume and the internal logical volume can be changed when the control program 3-19 writes a required information on the logical block assigned in the region
25 3-23. (This procedure will be explained in connection with the step 2 later.)

Details of processing effected by the operations in step 1 will be disclosed herein.

The application program 3-12 to be executed in the host computer 3-2 calls out the API 3-18 for reading out the configuration information 3-17 of the storage control device 3-1 (3-24).

5 Similarly, the control program 3-19 to be executed in the host computer 3-2 recognizes the indication for reading out of the configuration information 3-17 by the fact that the API 3-18 is called. Then, the program 3-19 issues, to the host
10 logical volume (for control) 3-11, a command for reading out the region 3-22 to be used for the function for reading out the configuration information 3-17 in the host logical volume (for control) 3-11 through the HBA 3-21 and the port 3-15 (3-25).

15 The command received on the side of the channel adapters is processed by the program executed by the microprocessor in the channel adapter.

The program is operated on the basis of the flow chart as shown in FIG. 6 every time the command is
20 received from the host computer 3-2. First, the reception of the command is detected (6-1).

Then, the program checks the kind of the host logical volumes (for control or for data) (6-2). This can be effected by examining the configuration
25 information of the host logical volume held in the configuration information 3-17 by the use of the number of the host logical volume contained in the command.

As a result, the program can identify whether

the relevant host logical volume is for control or data (6-3). As the command has been issued for the host logical volume (for control) 3-11 in the step 1, the host logical volume is judged it to be for control.

5 Thereafter, the program checks the kind (reading, writing or others) of the command (6-4). This is effected by checking command codes included in the command.

 As a result, the program can identify the
10 kind of command (reading, writing or others) (6-5). As the command has been issued for reading the region 3-22 in the host logical volume (for control) 3-11 in the step 1, the kind of the command is judged to be "reading".

15 Then, the program checks which region in the relevant host logical volume (for control) 3-11 (6-6) should be read out. This is effected by checking the numbers of the logical block contained in the command.

 As the result, the program can know the
20 processing to be effected (6-7). As the region 3-22 assigned for reading performance for the configuration information 3-17 is designated in the step 1, the processing to be effected is judged to be "reading of the configuration information 3-17". Then, the program
25 performs the configuration information reading processing 6-8.

 The configuration information reading processing 6-8 is effected by the configuration

information reading portion 3-20 which is part of the program executed by the microprocessor in the channel adapter.

The configuration information reading portion
5 3-20 reads the configuration information 3-17 held in the shared memory 3-16 (3-26).

The configuration information reading portion 3-20 sends the read configuration information 3-17, as a response to the command for reading the region 3-22
10 (3-27), to the control program 3-19 through the path through which the command has been issued.

The control program 3-19 sends the configuration information 3-17 obtained from the interior of the storage control device 3-1 to the
15 application program 3-12 which has called the API 3-18 for reading the configuration information 3-17 (3-28).

In this manner, the application program 3-12 obtains the configuration information 3-17 in the storage control device 3-1 described above, whereby the
20 application program 3-12 can know 1) the configuration of the host logical volume, 2) the configuration of the internal logical volume, and 3) the mapping between the host logical volume and the internal logical volume.

Details of processing effected by the
25 operation in step 2 will be disclosed herein.

The application program 7-12 to be executed in the host computer 7-2 calls out the API 7-18 for changing the mapping between the host logical volume

and the internal logical volume in the storage control device 7-1 (7-24).

Similarly, the control program 7-19 to be executed in the host computer 7-2 recognizes the
5 indication for changing the mapping between the host logical volume and the internal logical volume by the fact that the API 7-18 has been called. The control program 7-19 sends a command for writing information required for changing the mapping between the host
10 logical volume and the internal logical volume (the number of the host logical volume to be changed and the number of the internal logical volume to be newly mapped thereto) to the region 7-22 which is in the host logical volume (for control) 7-11 and to be used for
15 the change mapping between the host logical volume and the internal logical volume. This command is sent through the HBA 7-21 and the port 7-15 to the host logical volume (for control) 7-11 (7-25).

The command received on the side of the
20 channel adapters is processed by the program executed by the microprocessor in the channel adapter.

As described above, the program is operated on the basis of the flow chart as shown in FIG. 6 every time the command is received from the host computer 7-
25 2. First, the reception of the command is detected (6-1).

Then, the program checks the kind of the host logical volume (for control or for data) (6-2). This

can be effected by examining the configuration information of the host logical volume held in the configuration information 3-17 by the use of the number of the host logical volume contained in the command.

5 As a result, the program can identify whether the relevant host logical volume is for control or data (6-3). As the command has been issued for the host logical volume (for control) 3-11 in the step 2, the host logical volume is judged to be for control.

10 Thereafter, the program checks the kind (reading, writing or others) of the command (6-4). This is effected by checking command codes included in the command.

 As a result, the program can identify the
15 kind of command (reading, writing or others) (6-5). As the command for writing on the region 7-22 in the host logical volume (for control) 7-11 has been issued in the step 2, the kind of the command is judged to be "writing".

20 Then, the program checks on which region in the relevant host logical volume (for control) 7-11 should be written (6-9). This is effected by checking the numbers of the logical block contained in the command.

25 As a result of this, the program knows the processing to be performed (6-10). In the step 2, as the region 7-23 is designated as a region assigned for the function for changing the mapping between the host

logical volume and the internal logical volume, the processing to be performed is judged to be the change mapping between the host logical volume and the internal logical volume. Then, the program carries out
5 the processing 6-11 for changing the mapping between the host logical volume and the inner logical volume.

The processing 6-11 for changing the mapping between the host logical volume and the internal logical volume is carried out by a mapping change
10 control and power control portion 7-14 which is part of the program to be executed by the microprocessor in the channel adapter.

The mapping change control and power control portion 7-14 carries out the processing for changing
15 the mapping between the host logical volume and the internal logical volume on the basis of a flow chart as shown in FIG. 8.

A processing performed at the beginning is the examination of the information written on the
20 region 23 (the number of the host logical volume to change its mapping and the number of the internal logical volume to be newly mapped thereto) (8-1).

Next, carried out is to check whether there is (are) other internal logical volume(s) mapped to
25 other host logical volume(s) in the ECC group including the internal logical volume mapped to the host logical volume designated in the region 7-23 (8-2). This examination is effected by retrieving a table holding

the numbers of the ECC groups exemplarily shown in FIG. 5 and the numbers of the internal logical volumes included in the respective relevant ECC groups.

When it is judged that there is no other
5 internal logical volume as a result of the retrieval of the tables exemplarily shown in FIG. 5, the program causes the host logical volume designated in the region 7-23 to stop a spindle motor of the HDD belonging to the ECC group including the internal logical volume
10 presently in the mapping relation (8-3). This is effected by a command for stopping the spindle motor, which is sent from the program to be executed in the microprocessor in the channel adapter to the HDD belonging to the relevant ECC group (7-26). Explaining
15 the command for stopping the spindle motor with reference to FIG. 2, the command is sent from the port 2-8 of the disk adapter 2-7 through the FC-A1 of fiber channel connecting the HDD 2-6, or fabric or parallel SCSI or ATA, S-ATA or the like.

20 There is a rotating time of the spindle motor as an element for determining MTBF which is a parameter of reliability of the HDD. As disclosed in the present invention, the time presumed from the MTBF till fault occurs can be prolonged by stopping the spindle motor.
25 As it has been known that there is no host logical volume mapped to the internal logical volume in the relevant ECC group, it can be regarded that there is no access from the host computer and therefore if the

spindle motor of the HDD belonging to the relevant ECC group is stopped, the host computer can be operated without any problem.

A configuration as shown in FIG. 9 is used to
5 hold the numbers of the ECC groups having the HDD of which spindle motor is rotating and the numbers of the internal logical volumes provided by its ECC groups. It may be regarded that there is HDD having a rotating spindle motor in the ECC group having the configuration
10 coupled at a pointer, and number held in the configuration.

The configuration exemplarily as shown in FIG. 9 is held as one of the configuration information 7-17 in the shared memory 7-16.

15 The processing to be carried out next by the program is to remove the information concerning the ECC group, to which the HDD having the stopped spindle motor belongs, from the configuration existing in the configuration information 7-17 as shown in FIG. 9.

20 Therefore, the processing to be carried out by the program is to change state of the HDDs of ECC including relevant internal logical volume as "STOPPED" or to update the configuration information 7-17 so that there is no HDD having a rotating spindle motor, as a result
25 of the above removal of the information (8-4).

The configuration indicating the internal logical volume currently mapped to the host logical volume designated in the region 7-23 is the

configuration 9-1 in FIG. 9. And the configuration indicating the ECC group to which the internal logical volume belongs is the configuration 9-2.

Therefore, in order to update the
5 configuration as exemplarily illustrated in FIG. 9 by the program, removed is the information concerning the ECC group to which the HDD belongs, in which HDD the spindle motor has been stopped. In other words, the portion 9-3 surrounded by dotted lines is removed.
10 This is concretely effected by replacing pointers by new one by the program. (The pointers 9-4 and 9-5 are removed and the pointer 9-6 is newly set.)

In this manner, the information concerning the ECC group containing the internal logical volume
15 currently mapped to the host logical volume designated in the region 7-23 is removed resulting in the state that in the relevant ECC, there is no HDD in which a rotating spindle motor has been stopped.

Then, the program checks whether the spindle
20 motor is rotating, which is of the HDD in the ECC group including the internal logical volume designated to be newly mapped to the host logical volume designated in the region 7-23 (8-5). This is effected by retrieving the configuration as exemplarily shown in FIG. 10 (the
25 same configuration in FIG. 9, although being divided for convenience of explanation) included in the configuration 7-17. If the number of the relevant ECC group is found in the configuration exemplarily shown

in FIG. 10, the spindle motor of the HDD in the ECC group is rotating.

If it is judged that the spindle motor of the HDD is not rotating, whose HDD is in the ECC group
5 containing the internal logical volume designated to be newly mapped to the host logical volume designated in the region 7-23, the program causes to rotate the spindle motor of the HDD belonging to the ECC including the internal logical volume now mapped to the host
10 logical volume designated in the region 7-23 (8-6).

In the similar manner to the stoppage of the spindle motor of the HDD described above, this is effected by sending a command for rotating the spindle motor from the program to be executed in the
15 microprocessor in the channel adapter to the HDD belonging to the relevant ECC group (7-26). Explaining the command for stopping the spindle motor with reference to FIG. 2, the command is sent from the port 2-8 of the disk adapter 2-7 through the FC-AL of fiber
20 channel connecting the HDD 2-6, fabric or parallel SCSI, or ATA, SATA or the like.

The next processing to be effected by the program is to add the information concerning the ECC group to which the HDD belongs, whose spindle motor has
25 been rotated, from the configuration in the configuration information 7-17 as exemplarily shown in FIG. 10 to change state of the HDDs in ECC including designated internal logical volume as "ROTATING" or to update the

configuration information 7-17 in a manner that there is the HDD having the rotating spindle motor in the relevant ECC group (8-7).

If the portion 10-1 surrounded by dotted
5 lines in FIG. 10 is the configuration illustrating the ECC group of which spindle motor is newly rotated and the internal logical volume newly designated to be mapped to the host logical volume designated in the region 7-23, the program deletes the present pointer
10 10-2 and newly sets pointers 10-3 and 10-4.

In this manner, the portion surrounded by the dotted lines is incorporated in the configuration holding the number of the ECC group having the HDD in which the spindle motor is rotating as exemplarily
15 shown in FIG. 10 and the number of the internal logical volume provided by its ECC group so that thereafter it is regarded that the spindle motor of the HDD in the relevant ECC group is rotating.

Then, the next processing to be effected by
20 the program is to bring the internal logical volume designated in the region 7-23 into the mapping relation to the host logical volume designated in the region 7-23 in the change-over portion 7-13 (7-28).

This is effected by updating configuration
25 information to map the designated internal logical volumes to designated host logical volume newly or by updating the table for holding mapping of the number of the host logical volume and the number of the internal

logical volume mapped to the host logical volume as exemplarily shown in FIG. 4 (8-8).

As disclosed in detail described above, the configuration of the host logical volume and the mapping of the internal logical volume are modified without varying the configuration of the host logical volume recognized by the host computer at all. This process makes it possible to access a plurality of (internal) logical volumes different in content from the side of the host computer through the host logical volume having the same identifier without any operation for again recognizing the host logical volume on the side of the host computer.

In the second method, instead of the application program 3-12 in the host computer 3-2, an operator of the host computer 3-2 directly operates the User Interface (UI) 3-29 of the control program 3-19 to change the mapping between the host logical volume and the internal logical volume.

The operator of the host computer 3-2 can designate the information which was given through the API 3-18 by the application program, that is, 1) the number of the host logical volume as an object to be changed, and 2) the number of the internal logical volume to be newly into mapped thereto.

Moreover, the operator of the host computer 3-2 can obtain, through the UI 3-29, the information which was obtained by the application program through

the API 3-18, that is, 1) the configuration of the host logical volume, 2) the configuration of the internal logical volume, and 3) the mapping between the host logical volume and the internal logical volume.

5 In the second method, the operation for the control program 3-19 is only changed from the API 3-18 to the UI 3-29, but the interface between the control program 3-19 and the host logical volume (for control) 3-11 is exactly the same. Therefore, the same are the
10 operation for obtaining the configuration information 3-17 in the storage control device 3-1 in the step 1 disclosed above, the operation of the program in the channel adapters in the storage control device 3-1 for changing the mapping between the host logical volume
15 and the internal logical volume in step 2, and the operation of the program in the disk adapter.

The second embodiment will then be explained.

There are two different features from the embodiment already explained.

20 The first different feature of the present embodiment is no use of the host logical volume (for control) 7-11 as in FIG. 7. Instead of the host logical volume (for control) 7-11, API for control 11-11 provided in the storage control device is used. The
25 API for control 11-11 is provided by the program equipped in the storage control device 11-1. This program is operated in 1) the channel adapter equipped in the storage control device 11-1 or 2) service

processor equipped in the storage control device 11-1.

The second difference of the present embodiment concerns with the transfer path of control information between the storage control device 11-1 and
5 the host computer 11-2. In the embodiment already explained, the control program 7-19 carries out the reading the configuration information and writing the control information with respect to the host logical volume (for control) through the HBA 7-21 and the port
10 7-15. On the other hand, in the second embodiment, the control program 11-19 calls the control API 11-11 through the network interface card (NIC) 11-24 and the port 11-25 on the side of the storage control device 11-1 instead of the HBA 11-21 to carry out the reading
15 of the configuration information and writing of the control information.

Although there are two differences described above, the basic processes of the reading out of the structural information 11-20 and the change mapping
20 between the host logical volume and the internal logical volume are substantially similar to those in the embodiment already explained.

Next, the third embodiment will be disclosed.

In the embodiments already explained, a
25 plurality of the HDD are divided into the ECC groups as shown at ECC group 2-12 in FIG. 2 and the memory regions made by the ECC groups are divided into one or plural regions to form the internal logical volumes,

and the internal logical volumes are brought into mapping relation to the host logical volume. In the present embodiment, one HDD is used instead of the ECC groups without using the internal logical volumes

5 provided by the ECC groups. The memory region made by the one HDD is divided into one or plural regions to form internal logical volumes which are then brought into the mapping relation to the host logical volume.

The third embodiment is substantially similar
10 to the embodiments already explained with the exception that one HDD is used instead of the ECC groups.

In either case, the storage control device for storing data to be processed by the host computer is effective in utilizing the device for back-up and
15 restoring of data or in utilizing as the archive.

Although the configuration of carrying out the present invention is explained using the HDD having the S-ATA as interconnection interface, it is to be understood that the invention is not limited to such a
20 configuration and may be applicable to storage control devices utilizing other HDD's.

While the invention has been explained with reference to embodiments thereof which are intended to make the invention be easily understood and not to
25 limit the invention. The invention can be modified and improved without departing from the spirit and scope of the invention and includes equivalents and the like in its scope.